



Evolution Wireless Digital EW-DP SKP | Digital plug-on transmitter



Digital UHF XLR plug-on transmitter featuring +48V phantom power, microSD card slot, and 3.5 mm lav mic input for use with Evolution Wireless Digital.

FEATURES

- Fully digital UHF wireless microphone system for video applications
- Integrated Bluetooth for synchronization and control
- Smart Notifications for troubleshooting and system guidance
- Intelligent battery management provides operating time (hours:minutes)
- Extended battery life: up to 12h on transmitter, 7h on receiver (SKP up to 6h)
- Magnetically stackable components for versatile mounting
- Industry leading 134 dB dynamic range for distortion free transmission
- Up to 56 MHz bandwidth for flexibility in any RF environment
- Exceptionally low latency (1.9 ms)
- External charging and powering via USB-C (receiver only)
- Smart Assist app for monitor & control
- Optional plug-on transmitter features XLR & 3.5 mm inputs, +48V & recording via microSD (ENG Set or component only)

DELIVERY INCLUDES

- EW-DP SKP digital plug-on transmitter
- 2 AA batteries



Evolution Wireless Digital

EW-DP SKP | Digital plug-on transmitter

SPECIFICATIONS

System		EW-DP SKP		
Audio link frequency ranges	Q1-6	470.2 – 526 MHz	Input voltage	~ 2.0 - 4.35 V
	R1-6	520 – 576 MHz	Input current	< 300 mA / (without record and P48)
	R4-9	552 – 607.8 MHz	Power Supply	2x AA batteries 1.5 V or BA 70 rechargeable battery pack
	S1-7	606.2 – 662 MHz		
	S4-7	630 – 662 MHz	Transmit power	Audio link: 10 mW ERP BLE: max. 10 mW EIRP
	S7-10	662 – 693.8 MHz		
	T1/7	694.5 – 702.7 MHz & 748.3 – 757.7 MHz	Audio output power	< 2 dBV max. (high level) / < 4 dBu max (high level)
	T12	806.125 – 809.750 MHz		
	T13-14	819.2 – 823.0 MHz	Output power XLR	max. 10 mA
	U1/5	823.2 – 831.8 MHz & 863.2 – 864.8 MHz		
	V3-4	925.2 – 937.3 MHz	Dimensions	108 x 42 mm
	Y1-3	1785.2 – 1799.8 MHz		
	Bluetooth® Low Energy (BLE) frequency range	2402 - 2480 MHz	Weight (without batteries)	ca. 163 g (0.36 lbs)
Audio frequency response	20 Hz - 20 kHz (-3 dB) @ 3 dBfs			
Audio THD	≤ -60 dB for 1 kHz @ -3 dBfs input level			
Dynamic range	134 dB			
System latency	1.9 ms			
Operating temperature	-10 °C - +55 °C (14 °F - 131 °F)			
Relative humidity	5 - 95 % (non-condensing)			

PRODUCT VARIANTS

EW-DP SKP (Q1-6)	470.2 – 526 MHz	Art. no. 700080
EW-DP SKP (R1-6)	520 – 576 MHz	Art. no. 700081
EW-DP SKP (R4-9)	552 – 607.8 MHz	Art. no. 700082
EW-DP SKP (S1-7)	606.2 – 662 MHz	Art. no. 700083
EW-DP SKP (S4-7)	630 – 662 MHz	Art. no. 700084
EW-DP SKP (S7-10)	662 – 693.8 MHz	Art. no. 700085
EW-DP SKP (T1/7)	694.5 – 702.7 MHz & 748.3 – 757.7 MHz	Art. no. 700478
EW-DP SKP (T12)	806.125 – 809.750 MHz	Art. no. 700479
EW-DP SKP (T13-14)	819.2 – 823.0 MHz	Art. no. 700480
EW-DP SKP (U1/5)	823.2 – 831.8 MHz & 863.2 – 864.8 MHz	Art. no. 700086
EW-DP SKP (V3-4)	925.2 – 937.3 MHz	Art. no. 700088
EW-DP SKP (Y1-3)	1785.2 – 1799.8 MHz	Art. no. 700089



Evolution Wireless Digital

EW-DP SKP | Digital plug-on transmitter

ACCESSORIES

Mounting Plate Set	Mounting kit for EW-DP (Mounting plate, mounting screws, cold shoe mount, allen key, and belt clip)	Art. no. 700005
Mounting Plate	Single mounting plate	Art. no. 588188
CL35	3.5 mm to 3.5 mm TRS coiled cable	Art. no. 586365
CL35-Y	3.5 mm to dual-3.5 mm TRS coiled cable	Art. no. 700061
CL35XLR	3.5 mm to XLR plug coiled cable	Art. no. 700062
BA 70	Rechargeable battery pack for SK,SKM-S, SKP	Art. no. 508860
L 70 USB	Charger for BA 70 rechargeable battery pack	Art. no. 508861
EW-D CHARGING SET	Set of L 70 USB charger and 2 BA 70 rechargeable battery packs	Art. no. 508862

DIMENSIONS

EW-DP SKP

